

RADIO TEST REPORT

For

Shenzhen Wesion Technology Co., Ltd.

VIM3

Test Model: VIM3 Basic

Additional model: Please refer to page 6

Prepared for : Shenzhen Wesion Technology Co., Ltd.
Address : A#511, Mingyou Purchasing Center, Baoyuan Rd., Xixiang St.,
Bao'an Dis., Shenzhen, China.

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : Room 101, 201, Building A and Room 301, Building C, Juji
Industrial Park, Yabianxueziwei, Shajing Street, Bao' an
District, Shenzhen, Guangdong, China.

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : March 27, 2020
Number of tested samples : 1
Serial number : Prototype
Date of Test : March 27, 2020 ~ April 08, 2020
Date of Report : April 17, 2020

RADIO TEST REPORT

MIC Notice No.88 Appendix No. 43

Second-Generation Low-Power Data Communication System/Wireless LAN System

Report Reference No. : LCS200319044AEB

Date of Issue..... : April 17, 2020

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address..... : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao' an District, Shenzhen, Guangdong, China.

**Testing Location/ Procedure : Full application of Harmonised standards ☒
Partial application of Harmonised standards ☐
Other standard testing method ☐**

Applicant's Name : Shenzhen Wesion Technology Co., Ltd.

Address..... : A#511, Mingyou Purchasing Center, Baoyuan Rd., Xixiang St., Bao'an Dis., Shenzhen, China.

Test Specification

Standard..... : MIC Notice No.88 Appendix No.43

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : VIM3

Trade Mark..... : Khadas

Test Model..... : VIM3 Basic

Ratings..... : Input: 5V \Rightarrow 3A, 9V \Rightarrow 2.67A, 12V \Rightarrow 2A

Result : Positive

Compiled by:

Supervised by:

Approved by:

Jayden Zhuo

Jin Wang



Jayden Zhuo/ File administrators

Jin Wang/ Technique principal

Gavin Liang/ Manager

RADIO -- TEST REPORT**Test Report No. : LCS200319044AEB**April 17, 2020

Date of issue

Test Model..... : VIM3 Basic

EUT..... : VIM3

Applicant..... : Shenzhen Wesion Technology Co., Ltd.Address..... : A#511, Mingyou Purchasing Center, Baoyuan Rd., Xixiang St.,
Bao'an Dis., Shenzhen, China.

Telephone..... : /

Fax..... : /

Manufacturer..... : Shenzhen Wesion Technology Co., Ltd.Address..... : A#511, Mingyou Purchasing Center, Baoyuan Rd., Xixiang St.,
Bao'an Dis., Shenzhen, China.

Telephone..... : /

Fax..... : /

Factory..... : /

Address..... : /

Telephone..... : /

Fax..... : /

Test Result**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
000	April 17, 2020	Initial Issue	Gavin Liang

TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. DESCRIPTION OF DEVICE (EUT)	6
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS	7
1.3. EXTERNAL I/O CABLE	7
1.4. DESCRIPTION OF TEST FACILITY	7
1.5. TEST CONDITIONS	7
1.6. FREQUENCY OF CHANNELS	7
2. TEST METHODOLOGY	8
2.1. EUT EXERCISE	8
2.2. MEASUREMENT UNCERTAINTY	8
2.3. TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING	8
2.4. DESCRIPTION OF TEST MODES	8
2.5. TEST VOLTAGE	8
3. SYSTEM TEST CONFIGURATION	9
3.1. JUSTIFICATION	9
3.2. EUT EXERCISE SOFTWARE	9
3.3. SPECIAL ACCESSORIES	9
3.4. BLOCK DIAGRAM/SCHEMATICS	9
3.5. EQUIPMENT MODIFICATIONS	9
4. SUMMARY OF TEST RESULTS	10
5. TEST RESULT	11
5.1. ANTENNA POWER	11
5.2. FREQUENCY TOLERANCE	13
5.3. OCCUPIED FREQUENCY BANDWIDTH	17
5.4. SPREAD BANDWIDTH	21
5.5. TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED)	25
5.6. CARRIER SENSING FUNCTION	35
5.7. INTERFERENCE PREVENTION FUNCTION	36
5.8. SECONDARY RADIATED EMISSIONS	37
6. PHOTOGRAPHS OF TEST SETUP	40
7. EXTERNAL PHOTOGRAPHS OF THE EUT	41
8. INTERNAL PHOTOGRAPHS OF THE EUT	45
9. LIST OF MEASURING EQUIPMENTS	48

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: VIM3
Test Model	: VIM3 Basic
Additional Model No:	: VIM3 Pro, VIM3L
Model Declaration:	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Hardware Version	: V12
Software Version	: Android 9.0
Power Supply	: Input: 5V=3A, 9V=2.67A, 12V=2A

Bluetooth

Frequency Range	: 2402-2480MHz for Bluetooth (79 channels for Bluetooth V5.0(BDR/EDR) : 40 channels for Bluetooth V5.0(BT LE) Channel Frequency=2402+(K-1), K=1, 2, 379 Channel Frequency=2402+2(K-1), K=1, 2, 340
Declared Antenna Power	: Bluetooth V5.0(BDR/EDR): 0.03mW/MHz : Bluetooth V5.0(BT LE): 0.7mW
Modulation Technology	: Bluetooth V5.0(BDR/EDR): GFSK, $\pi/4$ -DQPSK, 8-DPSK : Bluetooth V5.0(BT LE): GFSK
Data Rate	: Bluetooth V5.0(BDR/EDR): 1/2/3Mbps : Bluetooth V5.0(BT LE): 2Mbps
Antenna Description	: FPC Antenna, 2.00dBi

WIFI(2.4G Band)

Frequency Range	: 2412-2472MHz
Channel Spacing	: 5MHz
Channel Number	: 2412-2472MHz: : 13 channels for 20MHz bandwidth(2412~2472MHz) IEEE 802.11b: 1.5mW/MHz
Declared Antenna Power	: IEEE 802.11g: 1.5mW/MHz IEEE 802.11n HT20: 4.5mW/MHz
Modulation Type	: IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK); : IEEE 802.11g/n: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11b: 11/5.5/2/1Mbps.
Data Rate	: IEEE 802.11g: 54/48/36/24/18/12/9/6Mbps. IEEE 802.11n HT20: 65.0/58.5/52.0/39.0/26.0/19.5/13.0/6.5Mbps
Antenna Description	: ANT 0: FPC Antenna, 2.00dBi : ANT 1: FPC Antenna, 2.00dBi

WIFI(5.2G Band)

Frequency Range	: 5180-5240MHz 4 channels for 20MHz bandwidth(5180~5240MHz)
Channel Number	: 2 channels for 40MHz bandwidth(5190~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Declared Antenna Power	: IEEE 802.11a: 2.0mW/MHz : IEEE 802.11n HT20: 2.0mW/MHz

	IEEE 802.11n HT40: 1.0mW/MHz
	IEEE 802.11ac VHT20: 2.0mW/MHz
	IEEE 802.11ac VHT40: 1.0mW/MHz
	IEEE 802.11ac VHT80: 1.0mW/MHz
Modulation Type	: IEEE 802.11a/n/ac: OFDM(64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: ANT 0: FPC Antenna, 2.00dBi
	: ANT 1: FPC Antenna, 2.00dBi

1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
--	--	--	--	--

1.3. External I/O Cable

I/O Port Description	Quantity	Cable
HDMI Port	1	USB Cable: 1m, unshielded
Type C Port	1	USB Cable: 1m, unshielded
USB Cable	2	USB Cable: 0.8m, unshielded

1.4. Description of Test Facility

FCC Registration Number is 254912.

Industry Canada Registration Number is 9642A-1.

EMSD Registration Number is ARCB0108.

UL Registration Number is 100571-492.

TUV SUD Registration Number is SCN1081.

TUV RH Registration Number is UA 50296516-001.

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

1.5. Test Conditions

Temperature Range	:	21-25℃
Humidity Range	:	45-85%
Pressure Range	:	86-106kPa

1.6. Frequency of Channels

Bluetooth V5.0 (BT LE)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2402	21	2442
2	2404	---	---
3	2406	---	---
---	---	38	2476
---	---	39	2478
19	2438	40	2480
20	2440		

2. TEST METHODOLOGY

2.1. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of MIC Notice No.88 Appendix No. 43.

2.2. Measurement Uncertainty

Test Item		MU	Remark
Bandwidth	:	+/- 0.2 E-6	/
Antenna Power	:	+/-0.33dB	/
Frequency Tolerance	:	+/- 0.3 E-6	/
Conducted spurious emission	:	+/-0.13dB	/
DC Power	:	+/-1%	/

- (1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.3. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters:

Test Software Version	QN908x-Programming-Tool		
Frequency	2402MHz	2440MHz	2480MHz
Bluetooth V5.0(DTS)	Default	Default	Default

2.4. Description of Test Modes

Tested mode, channel, and data rate information				
Mode	Preliminary Test Data Rate (Mbps)	Final Test Data Rate (Mbps) (see Note)	Channel	Frequency (MHz)
Bluetooth V5.0 (BT LE)	2	2	Low :CH1	2402
	2	2	Middle: CH20	2440
	2	2	High: CH40	2480
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.				

2.5. Test Voltage

POWER SUPPLY VOLTAGE FLUCTUATION TEST

Environment	Input Voltage(DC)
-10%	DC 10.8V
Normal	DC 12V
+10%	DC 13.2V

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in engineering mode.

3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software provided by application.

3.3. Special Accessories

N/A.

3.4. Block Diagram/Schematics

Please refer to the related document.

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

4. SUMMARY OF TEST RESULTS

MIC Notice No.88 Appendix No.43 Article 2 Paragraph 1 Item 19		
Clause	Description of Test (Transmitter Parameters)	Result
6	Antenna Power	PASS
6	Tolerances for Antenna Power	PASS
3	Frequency Tolerance	PASS
4	Transmission Rate	PASS
4	Occupied Frequency Bandwidth	PASS
4	Spread Bandwidth	PASS
13	Dwell Time	N/A
5	Spurious Emissions	PASS
10	Transmission Antenna Gain (EIRP Antenna Power)	N/A
11	Transmission Radiated Angle Width (3dB Beam width)	N/A
12	Interference prevention function	PASS
8	Carrier Sensing function	N/A
Receiver Parameters		
7	Secondary Radiated Emissions	PASS
<p><i>Note: (1) N/A is an abbreviation for Not Applicable.</i></p> <p><i>(2) N/T means this test item is not tested.</i></p> <p><i>(3) This is a DTS test report for VIM3(VIM3 Basic), please refer to other document for the DSS test report.</i></p>		

5. TEST RESULT

5.1. Antenna Power

5.1.1. Standard Applicable

Type	Limit
DTS	10mW
OFDM OBW<26MHz, DS	10mW/MHz
OFDM OBW 26-38MHz	5mW/MHz
Tolerance	+20%,-80%


5.1.2. Measuring Instruments

Please refer to section 6 of equipments list in this report.

5.1.2. Test Procedures

- EUT have transmitted continuous maximum power
- Antenna Power Error is definition that actual measure antenna power tolerance between +20% to -80% power range that base on manufacturer declare the conducted power density.

5.1.3. Test Setup



5.1.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.5. Test Result

Temperature	22.5℃	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	Normal Voltage

Mode	CH	Declared Antenna Power	Result	Tolerance	Limit
		(mW)	(mW)		
Bluetooth V5.0(BT LE)	CH1	0.8	0.702	-12.24%	+20%,-80%
	CH20	0.8	0.474	-40.70%	+20%,-80%
	CH40	0.8	0.278	-65.30%	+20%,-80%

Temperature	22.5℃	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	Low Voltage

Mode	CH	Declared Antenna Power	Result	Tolerance	Limit
		(mW)	(mW)		
Bluetooth V5.0(BT LE)	CH1	0.7	0.696	-0.53%	+20%,-80%
	CH20	0.7	0.475	-32.10%	+20%,-80%
	CH40	0.7	0.276	-60.50%	+20%,-80%

Temperature	22.5℃	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	High Voltage

Mode	CH	Declared Antenna Power	Result	Tolerance	Limit
		(mW)	(mW)		
Bluetooth V5.0(BT LE)	CH1	0.7	0.701	0.11%	+20%,-80%
	CH20	0.7	0.478	-31.74%	+20%,-80%
	CH40	0.7	0.276	-60.55%	+20%,-80%

5.2. Frequency Tolerance

5.2.1. Standard Applicable

Tolerance of frequency shall be $\pm 50\text{ppm}$

5.2.2. Test Procedures

- a. Set EUT work in test mode as described in clause 2.4.
- b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 10 KHz.

Video BW: 10 KHz.


Span: 1MHz.

Detector: Peak.

Trace Mode: Max Hold.

- c. When the trace is complete, find the peak value of the power envelope and record.

5.2.3. Test Setup Layout



5.2.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.5. Test Result


Temperature	22.5℃	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	Normal Voltage

Bluetooth V5.0 (BT LE):


Channel	Frequency	Measured MHz	Tolerance KHz	Result ppm	Limit ppm
1	2402	2401.974	-26	-10.82	± 50
20	2440	2439.974	-26	-10.66	± 50
40	2480	2479.973	-27	-10.89	± 50

Test Plot Of Frequency Tolerance


Test Voltage: Normal Voltage



Low Channel



Middle Channel



High Channel


Temperature	22.5°C	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	Low Voltage

Bluetooth V5.0 (BT LE):


Channel	Frequency	Measured MHz	Tolerance KHz	Result ppm	Limit ppm
1	2402	2401.973	-27	-11.24	±50
20	2440	2439.973	-27	-11.07	±50
40	2480	2479.972	-28	-11.29	±50

Test Plot Of Frequency Tolerance


Test Voltage: Low Voltage



Low Channel



Middle Channel



High Channel



Temperature	22.5°C	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	High Voltage

Bluetooth V5.0 (BT LE):

Channel	Frequency	Measured MHz	Tolerance KHz	Result ppm	Limit ppm
1	2402	2401.973	-27	-11.24	±50
20	2440	2439.973	-27	-11.07	±50
40	2480	2479.972	-28	-11.29	±50


Test Plot Of Frequency Tolerance

Test Voltage: High Voltage



Low Channel

Middle Channel



High Channel

5.3. Occupied Frequency Bandwidth

5.3.1. Standard Applicable

Permissible value for occupied bandwidth using the FH system, a hybrid system combining DS and FH systems, or a hybrid system combining FH and OFDM systems shall be 83.5 MHz or less, while necessary bandwidth (minimum occupied bandwidth sufficient to ensure information transmission of required quality at a required transmission rate for the system used under specified conditions for a given emission type) using a system other than any of the above shall be 26 MHz or less.

5.3.2. Test Procedures

- a. Set EUT work in test mode as described in clause 2.4.
- b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

RBW/VBW= 30KHz/100KHz

Span: Wide enough to cover the complete power envelope of the signal of the EUT.


Sweep mode: Continuous sweeping.

Detector: Peak.

Trace Mode: Max Hold.

- c. When the trace is complete, measure the occupied bandwidth (99% bandwidth) with spectrum analyzer's bandwidth measure function.

5.3.3. Test Setup Layout



5.3.4. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

5.3.5. Test Result of 99% Spectrum Bandwidth


Temperature	22.5°C	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	Normal Voltage

Mode	CH	Result	Limit
		(MHz)	(MHz)
Bluetooth V5.0(BT LE)	CH1	2.0556	26
	CH20	2.0604	26
	CH40	2.0552	26

Test Plot Of 99% Spectrum Bandwidth



Low Channel



Middle Channel



High Channel

Note: Only record the worst result.

Temperature	22.5°C	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	Low Voltage


Mode	CH	Result	Limit
		(MHz)	(MHz)
Bluetooth V5.0(BT LE)	CH1	2.0552	26
	CH20	2.0607	26
	CH40	2.0530	26

Test Plot Of 99% Spectrum Bandwidth



Low Channel

Middle Channel





High Channel

Note: Only record the worst result.

Temperature	22.5°C	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	High Voltage


Mode	CH	Result	Limit
		(MHz)	(MHz)
Bluetooth V5.0(BT LE)	CH1	2.0550	26
	CH20	2.0603	26
	CH40	2.0618	26

Test Plot Of 99% Spectrum Bandwidth



Low Channel

Middle Channel



High Channel

Note: Only record the worst result.

5.4. Spread Bandwidth

5.4.1. Standard Applicable

In spread spectrum systems, spread bandwidth (which refers to a frequency bandwidth with an upper limit and lower limit such that each of the mean powers radiated above the upper frequency limit and below the lower frequency limit is equal to 5 % of the total mean power radiated; this also applies hereafter) shall be 500 kHz or more.

5.4.2. Test Procedures

- a. Set EUT work in test mode as described in clause 2.4.
- b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

RBW/VBW= 30 KHz/100KHz


Span: Wide enough to cover the complete power envelope of the signal of the EUT.

Detector: Peak.

Trace Mode: Max Hold.

- c. When the trace is complete, measure the occupied bandwidth (90% bandwidth) with spectrum analyzer's bandwidth measure function.

5.4.3. Test Setup Layout



5.4.4. EUT Operation during Test



The EUT was programmed to be in continuously transmitting mode.

5.4.5. Test Result of 90% Occupied Bandwidth.


Temperature	22.5°C	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	Normal Voltage

Mode	CH	Result	Limit
		(KHz)	(KHz)
Bluetooth V5.0(BT LE)	CH1	1330.2	>500
	CH20	1333.4	>500
	CH40	1325.4	>500

Test Plot Of 90% Occupied Bandwidth



Low Channel



Middle Channel


High Channel

Note: Only record the worst result.

Temperature	22.5°C	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	Low Voltage


Mode	CH	Result	Limit
		(KHz)	(KHz)
Bluetooth V5.0(BT LE)	CH1	1332.0	>500
	CH20	1334.0	>500
	CH40	1326.2	>500

Test Plot Of 90% Occupied Bandwidth



Low Channel

Middle Channel




High Channel

Note: Only record the worst result.


Temperature	22.5°C	Humidity	53.1%
Test Engineer	David Luo	Test Voltage	High Voltage

Mode	CH	Result	Limit
		(KHz)	(KHz)
Bluetooth V5.0(BT LE)	CH1	1330.8	>500
	CH20	1335.1	>500
	CH40	1326.0	>500


Test Plot Of 90% Occupied Bandwidth



Low Channel



Middle Channel



High Channel

Note: Only record the worst result.

5.5. Transmitter Spurious Emissions (conducted)

5.5.1. Standard Applicable

Permissible mean power of spurious emission of each frequency supplied to a feeder, that is, mean power of spurious emission in the 1 MHz bandwidth at frequency f other than frequency band used shall be as follows:

- a. $2,387\text{MHz} \leq f \leq 2,400\text{MHz}$ and $2,483.5\text{MHz} < f \leq 2,496.5\text{MHz}$ 25 μW or less
- b. $2,387\text{MHz} > f$ and $2,496.5\text{MHz} < f$ 2.5 μW or less

5.5.2. Test Procedures

- a. Set EUT work in test mode as described in clause 2.4.
- b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Below 1GHz: RBW/VBW= 100 KHz/ 100KHz


Above 1GHz: RBW/VBW= 1MHz / 1MHz.

Detector: Peak.

Trace Mode: Max Hold.

- c. All the emissions from 30MHz to 13GHz were measured and record.

5.5.3. Test Setup Layout



5.5.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



5.5.5. Test Results

Pass.


Test Plot Of Transmitter Spurious Emissions (conducted)

Temperature	22.5°C	Humidity	53.1%	Test Engineer	David Luo	Test Voltage	Normal Voltage
-------------	--------	----------	-------	---------------	-----------	--------------	----------------


TX CH1




30MHz-1000MHz




1000MHz-2387MHz



2387MHz-2400MHz




2483.5MHz-2497MHz




2497MHz-12.75GHz


TX CH20



30MHz-1000MHz




2387MHz-2400MHz




2497MHz-12.75GHz


TX CH40




30MHz-1000MHz



1000MHz-2387MHz



2387MHz-2400MHz




2483.5MHz-2497MHz


2497MHz-12.75GHz

Note: Only record the worst result.


Test Plot Of Transmitter Spurious Emissions (conducted)




TX CH20




30MHz-1000MHz




1000MHz-2387MHz



2387MHz-2400MHz




2483.5MHz-2497MHz




2497MHz-12.75GHz


TX CH40




30MHz-1000MHz



1000MHz-2387MHz



2387MHz-2400MHz




2483.5MHz-2497MHz


2497MHz-12.75GHz

Note: Only record the worst result.


Test Plot Of Transmitter Spurious Emissions (conducted)




TX CH20




TX CH40




30MHz-1000MHz




1000MHz-2387MHz



2387MHz-2400MHz



2483.5MHz-2497MHz



2497MHz-12.75GHz

Note: Only record the worst result.

5.6. Carrier sensing function

5.6.1. Standard Applicable

Item	Limits
Carrier Sense	Good - EUT stop RF transmission signal after carrier inject to EUT. (On $22.79 + Gr - 20 \cdot \log(f)$ [dBm] (Gr: dBi; f: MHz) or 100mV/m)

5.6.2. Instruments Setting


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	1 MHz
Span	0 MHz
Sweep	Continuous
Detector	Peak
Trigger mode	Video

5.6.3. Test Procedures

1. SSG adjusted the frequency as same as the EUT transmitted signal and emitted the absence of modulation from SSG and power level is (On $22.79 + Gr - 20 \cdot \log(f)$ [dBm] (Gr: dBi; f: MHz). Then turn off the RF signal of SSG.
2. EUT have transmitted the maximum modulation signal and fixed channelize.
3. Setting of SA is following as: RB: 1MHz / VB: 1MHz / SPAN: 50MHz / AT: 10dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak.
4. SSG RF Signal On.
5. EUT shall be stop the transmitted any signal and SSG RF Signal Off. Then EUT will be continuous transmitted signal.

5.6.4. Test Setup Layout



5.6.5. EUT Operation during Test

The EUT was programmed to be in normal transmitting mode.

5.6.6. Test Result

Not Applicable.

5.7. Interference prevention function

5.7.1. Standard Applicable

Item	Limits
Identification code	\geq 48 bits


5.7.2. Measuring ID Code Software

PC with NetTool	Setting
MAC IP List	MAC Scan

5.7.3. Test Procedures

1. In the case that the EUT has the function of automatically transmitting the identification code: a. Transmit the predetermined identification codes from EUT. b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code: a. Transmit the predetermined identification codes from the counterpart. b. Check if communication is normal. c. Transmit the other signals than predetermined ID codes from the counterpart. d. check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

5.7.4. Test Setup Layout



5.7.5. EUT Operation during Test

The EUT was programmed to be in normal transmitting mode.

5.7.6. Test Result

EUT ID	Performance index
32:7F:A9:F1:11:DA	Good

5.8. Secondary Radiated Emissions

5.8.1. Standard Applicable

The limit on secondary emissions radiated from the receiving equipment within which the function of other radio equipment will not be impaired shall be, in terms of the power of a dummy antenna circuit that has the same electrical constant as the receiving antenna, 4nW or less at a frequency below 1 GHz and 20 nW or less at a frequency of 1 GHz or higher as measured using the circuit

5.8.2. Test Procedures

- a. Set EUT work in test mode as described in clause 2.4.
- b. Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Resolution BW: 100 KHz for frequency below 1GHz and

1MHz for frequency above 1GHz

Video BW: 100 KHz for frequency below 1GHz and


1MHz for frequency above 1GHz

Detector: Peak.

Trace Mode: Max Hold.

- c. All the emissions from 30MHz to 13GHz were measured and record.

5.8.3. Test Setup



5.8.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.8.5. Test Results


Pass.

***Note: We found that RX (Low Channel) when input normal voltage was worst case through pre-scan, so this condition was recorded.

Test Plot Of Secondary Radiated Emissions

Temperature	22.5℃	Humidity	53.1%	Test Engineer	David Luo	Test Voltage	Normal Voltage
-------------	-------	----------	-------	---------------	-----------	--------------	----------------

RX CH1(BT LE)



30MHz-1000MHz

1000MHz-12.75GHz


Note: Only record the worst result.

***Note: We found that RX (Low Channel) when input 90% normal voltage was worst case through pre-scan, so this condition was recorded.

Test Plot Of Secondary Radiated Emissions

Temperature	22.5℃	Humidity	53.1%	Test Engineer	David Luo	Test Voltage	Low Voltage
-------------	-------	----------	-------	---------------	-----------	--------------	-------------

RX CH1(BT LE)



30MHz-1000MHz

1000MHz-12.75GHz



Note: Only record the worst result.

***Note: We found that RX (Low Channel) when input 110% normal voltage was worst case through pre-scan, so this condition was recorded.

Test Plot Of Secondary Radiated Emissions

Temperature	22.5℃	Humidity	53.1%	Test Engineer	David Luo	Test Voltage	High Voltage
-------------	-------	----------	-------	---------------	-----------	--------------	--------------

RX CH1(BT LE)





30MHz-1000MHz

1000MHz-12.75GHz

Note: Only record the worst result.

6. PHOTOGRAPHS OF TEST SETUP



Note: The RF cable is 50 ohm.

7. EXTERNAL PHOTOGRAPHS OF THE EUT




Fig. 1




Fig. 2




Fig. 3



Fig. 4




Fig. 5




Fig. 6



Fig. 7

8. INTERNAL PHOTOGRAPHS OF THE EUT




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6

9. LIST OF MEASURING EQUIPMENTS

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Meter	R&S	NRVS	100444	2019-06-11	2020-06-10
2	Power Sensor	R&S	NRV-Z81	100458	2019-06-11	2020-06-10
3	Power Sensor	R&S	NRV-Z32	10057	2019-06-11	2020-06-10
4	MXA Signal Analyzer	Agilent	N9020A	MY49100060	2019-11-22	2020-11-21
5	DC Power Supply	Agilent	E3642A	N/A	2019-11-14	2020-11-13

Note: All equipment is calibrated through CHINA CEPREI LABORATORY and GUANGZHOU LISAI CALIBRATION AND TEST CO., LTD.

-----THE END OF REPORT-----